

Electrical crimping tool - CF 1000-10 - 1212456

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Stripping and crimping machine, 120-230 V input voltage, electro-pneumatic, for loose ferrules with insulating collar, 4 mm², 6 mm², and 10 mm², without conversion kit

Product Features

- Quick change of cross section without the need for additional adjustments
- Up to 1200 conductors can be processed an hour
- Suitable for bulk processing
- Rugged design
- The pull-out forces meet the requirements of IEC/EN 60999 and IEC/EN 60947
- The stripping and crimping machine can be used to process loose ferrules with insulating collars according to DIN 46228-4
- The conductor is stripped in a single step and crimped with a ferrule to a high standard of quality
- Quantity counter

Key commercial data

Packing unit	1 pc
Custom tariff number	84798100
Country of origin	Germany

Technical data

Dimensions

Length (b)	490 mm
Height	390 mm
Width (a)	240 mm

General

Compression	trapezoidal
Air consumption per compression	1.2 l
Test standard	DIN 46228-4: 1990-09

Electrical crimping tool - CF 1000-10 - 1212456

Classifications

eCl@ss

eCl@ss 4.0	21040301
eCl@ss 4.1	21040301
eCl@ss 5.0	21040301
eCl@ss 5.1	21040301
eCl@ss 6.0	21043706
eCl@ss 7.0	21043706
eCl@ss 8.0	21043706

ETIM

ETIM 2.0	EC001186
ETIM 3.0	EC001186
ETIM 4.0	EC001186
ETIM 5.0	EC002778

UNSPSC

UNSPSC 6.01	30211811
UNSPSC 7.0901	39121410
UNSPSC 11	39121410
UNSPSC 12.01	39121410
UNSPSC 13.2	39121410