

RECOMMENDED P.C BOARD LAYOUT

NOTES:  
 SPECIFICATIONS:  
 CURRENT RATING:1 AMP.  
 VOLTAGE:250V AC/DC MAX.  
 DIELECTRIC WITHSTANDING:500VAC FOR ONE MINUTE.  
 CONTACT RESISTANCE:50mΩ (MAX).  
 INSULATION RESISTANCE:1000MΩ (MIN).  
 OPERATING TEMPERATURE:-55°C +105°C.  
 RETENTION FORCE:0.30KG PER PIN (MIN).  
 MATERIALS:  
 INSULATOR: PPS +30%GF UL 94V-0.  
 CONTACTS:PHOSOR BRONZE.  
 CONTACT PLATING TIN.


Dimension No. Of Pin	A	B	C	D	E	F	G	H
SMT-20P	15.65	15.65	5.08	5.08	9.35	9.35	10.03	10.03
SMT-28P	18.19	18.19	7.62	7.62	11.89	11.89	12.57	12.57
SMT-32P	20.65	18.15	10.16	7.62	14.35	11.85	13.56	12.80
SMT-44P	23.27	23.27	12.70	12.70	16.97	16.97	17.65	17.65
SMT-52P	25.81	25.81	15.24	15.24	19.51	19.51	20.19	20.19
SMT-68P	30.89	30.89	20.32	20.32	24.59	24.59	25.27	25.27
SMT-84P	35.97	35.97	25.40	25.40	29.67	29.67	30.35	30.35

DATE	DR.BY	EQN.NO.	DESCRIPTION	MARK	VER.
10/09/06	ING		NEW DWG		A0

-TOLERANCES-  
 UNLESS OTHERWISE SPECIFIED

公差参考表

Cnc Tech,LLC



TITLE: PLCC 0.20 SMT 成品

X.X	±0.30	X.X°	±3.00°	APPD:	PRODUCT NO:	232-XX
X.XX	±0.20	X.XX°	±1.00°	CHECK:	DATE	2010.09.06
X.XXX	±0.10	X.XXX°	±0.05°	DRAW:	SCALE	1:1
					UNIT	mm
					TYPE	Z
					PAGE	1/1