

## Base strip - PCV 6-16/ 8-G-10,16 - 1922543


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Header, Nominal current: 76 A, Number of positions: 8, Pitch: 10.16 mm, Color: green, Contact surface: Silver, Assembly: Soldering, The nominal current of 76 A applies in connection with connectors from the PC 16 family. 41 A are reached in connection with PC 6 connectors (50 A in accordance with UL).



### Key commercial data

Packing unit	1 pc
GTIN	 4 017918 727093
Weight per Piece (excluding packing)	30.28 GRM
Custom tariff number	85366990
Country of origin	Germany

### Technical data

#### Dimensions

Pitch	10.16 mm
Dimension a	71.12 mm

#### General

Range of articles	PCV 6-16/..-G
Rated voltage (III/3)	630 V
Connection in acc. with standard	EN-VDE
Nominal current $I_N$	76 A
Color	green
Number of positions	8

## Base strip - PCV 6-16/ 8-G-10,16 - 1922543

### Classifications

#### eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701
eCl@ss 6.0	27260704
eCl@ss 7.0	27440402
eCl@ss 8.0	27440402

#### ETIM

ETIM 3.0	EC001121
ETIM 4.0	EC002637
ETIM 5.0	EC002637

#### UNSPSC

UNSPSC 6.01	30211810
UNSPSC 7.0901	39121409
UNSPSC 11	39121409
UNSPSC 12.01	39121409
UNSPSC 13.2	39121409

### Approvals

#### Approvals

---

#### Approvals

UL Recognized / SEV / cUL Recognized / GOST / CCA / GOST / cULus Recognized

---

#### Ex Approvals

---

#### Approvals submitted

---

#### Approval details

# Base strip - PCV 6-16/ 8-G-10,16 - 1922543

## Approvals

UL Recognized			
	B	C	D
Nominal current IN	66 A	66 A	5 A
Nominal voltage UN	300 V	300 V	600 V

SEV	
Nominal current IN	76 A
Nominal voltage UN	1000 V

cUL Recognized			
	B	C	D
Nominal current IN	66 A	66 A	5 A
Nominal voltage UN	300 V	300 V	600 V

GOST	
------	--

CCA	
Nominal current IN	76 A
Nominal voltage UN	1000 V


GOST	
------	--

cULus Recognized	
------------------	--

## Drawings

# Base strip - PCV 6-16/ 8-G-10,16 - 1922543

Drilling diagram



Dimensioned drawing

