



APPLICABLE STANDARD				
RATING	OPERATING TEMPERATURE RANGE	-35 °C TO +85°C (NOTE1)	STORAGE TEMPERATURE RANGE	-10 °C TO +60°C (NOTE3)
	OPERATING HUMIDITY RANGE	20% TO 80% (NOTE2)	STORAGE HUMIDITY RANGE	40% TO 70% (NOTE3)
	VOLTAGE	350 V AC/DC	APPLICABLE CONTACT	DF61-2S-2.2C
	CURRENT	 AWG26 : 3.2 A	APPLICABLE CABLE	AWG26 TO AWG 30
INSULATION DIAMETER			φ0.7~1.3 mm	

### SPECIFICATIONS

ITEM	TEST METHOD	REQUIREMENTS	QT	AT
------	-------------	--------------	----	----


<b>CONSTRUCTION</b>				
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X
MARKING	CONFIRMED VISUALLY.		X	X

<b>ELECTRIC CHARACTERISTICS</b>				
CONTACT RESISTANCE	20 mV MAX, 1 mA(DC OR 1000 Hz).	10 mΩMAX.	X	-

<b>MECHANICAL CHARACTERISTICS</b>				
CONTACT INSERTION AND EXTRACTION FORCES	T=0.2±0.002 mm BY STEEL GAUGE.	INSERTION FORCE 5 N MAX. EXTRACTION FORCE 0.1 N MIN.	X	-
MECHANICAL OPERATION	30 TIMES INSERTION AND EXTRACTION.	① CONTACT RESISTANCE: 20 mΩ MAX. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	-
VIBRATION	FREQUENCY 10 TO 55 Hz, SINGLE AMPLITUDE 0.75 mm, AT 10 CYCLES FOR 3 DIRECTION.	① NO ELECTRICAL DISCONTINUITY OF 1 μs. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	-
SHOCK	490 m/s <sup>2</sup> DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.	② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	-
CRIMP TENSILE STRENGTH		#AWG26 : 18 N MIN. 	X	-



<b>ENVIRONMENTAL CHARACTERISTICS</b>				
DAMP HEAT(STEADY STATE)	EXPOSED AT 40 ± 2°C , 90 TO 95 %, 96 h. (AFTER LEAVING THE ROOM TEMPERATURE FOR 1~2h.)	① CONTACT RESISTANCE: 20 mΩ MAX. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	-
RAPID CHANGE OF TEMPERATURE	TEMPERATURE -55°C→ +85°C TIME 30min→ 30min UNDER 5 CYCLES. (AFTER LEAVING THE ROOM TEMPERATURE FOR 1~2h.)		X	-

NOTE 1: INCLUDE THE TEMPERATURE RISING BY CURRENT.  
 NOTE2:NO CONDENSING  
 NOTE3:APPLY TO THE CONDITION OF LONG TERM STORAGE FOR UNUSED PRODUCTS BEFOR PCB ON BOARD , AFTER PCB BOARD , OPERATING TEMPERATURE AND HUMIDITTY RANGE IS APPLIED FOR INTERIM STRAGE DURING TRANSPORTATION.

COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
 2	DIS-H-007449	ST. SATO	HK. UMEHARA	12. 11. 28
REMARKS			APPROVED	KI. AKIYAMA 12. 06. 14
			CHECKED	HK. UMEHARA 12. 06. 14
			DESIGNED	TT. OHSAKO 12. 06. 12
			DRAWN	TT. OHSAKO 12. 06. 12

Unless otherwise specified, refer to JIS C 5402.

Note QT:Qualification Test AT:Assurance Test X:Applicable Test	DRAWING NO.	ELC4-336117-02
--	-------------	----------------

	SPECIFICATION SHEET	PART NO.	DF61-2630SCF (41)	
	HIROSE ELECTRIC CO., LTD.	CODE NO.	CL666-5003-7-41	 1/1