



ⓑ NOTES:

1. METALSHELLS: STEEL; min. 315µin TIN over 40-80µin NICKEL
2. INSULATORS: PBT GF UL 94 V-0, BLACK
3. FRAME: STEEL; NICKEL PLATED
4. FLOAT MOUNTS: COPPER ALLOY; NICKEL PLATED
5. RIVETED INSERTS: COPPER ALLOY; min. 200µin TIN over 80µin NICKEL
6. COLLARS: COPPER ALLOY; min. 200µin TIN over 80µin NICKEL
7. CONNECTOR WILL BE SUPPLIED WITHOUT CONTACTS
8. CONNECTOR IS PART MARKED: 'DSS1XSXXB01X CONEC ABC'

Directive 2002/95/EC RoHS compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH				tolerance		dim. in mm	scale: 2:1 (5:1)	
				date			material: SEE NOTES	
DO NOT ALTER CAD DRAWING BY HAND				drawn	19.08.03	Lehmenkühler	title: D-SUB FEMALE 9pos. CRIMP STYLE with frame and float mount	
				appd.	19.08.03	Mickenbecker		
4 x c	Ä5047	16.01.2014	Lehm.	d-old	dwg no:			
2 x b	Ä3639	03.05.2010	Petker	norm		16K1A1002		sh: 1
a	Original			CONEC [®]		part no: DSS1XSXXB01X		
rev.	description	date	name					