


RECOMMENDED P.C.B. HOLES



CIRCUIT: SPDT

NOTES:

1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
3. TERM NOS. FOR REF. ONLY
4. RATING: 5A @120VAC or 28VDC (Resistive Load)
2A @250VAC
5. CONTACT MATERIAL: Copper ALloy w/Silver Plating
6. INSULATION RESISTANCE: 1000 Mega Ohms min.
7. DIELECTRIC STRENGTH: 1000V RMS @SEA LEVEL.
8. OPERATING TEMPERATURE: -30°C TO 85°C

SWITCH FUNCTION		
POS. 1	POS. 2	POS. 3
ON	NONE	ON
2-1	OPEN	2-3

E-SWITCH®

D 21656 EDIED DIMENSIONS 10/22/14 AS		C 12382 REVISED ACTUATOR 8/19/02 CJB		B 11547 REVISED ACTUATOR/NOTES 7/3/01 CJB		REV. ECN No. DESCRIPTION DATE CHKD	
TITLE				500 SSP-1 S3 M7 Q E A			
SCALE	DATE	DR	DWG	REV			
2:1	2/12/01	CJB	T511010	D			

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED