


Specification Sheet

Part Number: 181-15304



Slotted Wall Wiring Duct, 1.5" X 3", Non-Adhesive, PVC, Gray, 120ft/Carton

| | |
|---------------------|---|
| Article Number | 181-15304 |
| Type | SL1.5X3 |
| Color | Gray (GY) |
| Features & Benefits | <ul style="list-style-type: none">• Strong fingers prevent unwanted breaking.• Fingers are easily deflected outward, allowing ready positioning of the wires within the slotted wall duct.• Restricted opening prevents unintended removal of wires and permits any individual wire to be traced without disconnection. |
| Quantity Per | carton |

Product Description

Pro-Duct slotted wall wiring duct features break-away fingers which provide additional access for wire leads. Each section of the duct is provided with two score lines. The upper score line is used to break away fingers when a wider opening is required. The lower score line allows the sidewall to be smoothly cut for joints and "T's".

| | |
|---|--|
| Short Description | Slotted Wall Wiring Duct, 1.5" X 3", Non-Adhesive, PVC, Gray, 120ft/Carton |
| Global Part Name | SL1.5X3-PVC-GY |
| Technical Description | Non-Adhesive |
| Length L (Imperial) | 6.0 |
| Length L (Metric) | 1.83 |
| Width W (Imperial) | 1.5 |
| Width W (Metric) | 38.1 |
| Height H (Imperial) | 3.07 |
| Height H (Metric) | 77.90 |
| Mounting Hole Centers (Imperial) | 4.0 |
| Material | Polyvinylchloride (PVC) |
| Material Shortcut | PVC |
| Flammability | Self-Extinguishing |
| Halogen free | No |
| Operating Temperature (Metric) | +122°F (+50°C) |

Reach Complaint(Article 33)

No

ROHS Complaint

Yes

Certification/Specification WEB

EN 50085-1:2005 + A1:2013 CSA EN 50085-2-3_1A UL

UL Recognized (US)

Yes

Package Quantity(Imperial)

120

Package Quantity (Metric)

36.58

Customs Number

3925900000