

Laird Technologies

Web site: www.LairdTech.com

All Categories > Metallized Conductive Fabric > D-Shaped Gaskets > D-Sub Connector Series Standard I/O Gaskets > Square Shaped Gaskets > Rectangle Shaped Gaskets > UltraFlex D with PSA Copper Knitted Wire Shielding > All Mesh Round Strip EMI Gasketing > All Mesh Single Round with Fin Strip EMI Gasketing > ElectroGround EMI Washers > A-Base Antennas > Dual Band & Special Applications Antennas > ElectroMet Oriented Wire EMI Shielding Solutions > Mobile Accessories > Mobile Load Coil Antennas > Item # B2002N

Item # B2002N, Mobile Load Coil Antennas



[larger image](#)

Stock Locator

- Low loss coil form adds dimensional and frequency stability
- ABS material is injection molded around solid brass inserts to create a virtually indestructible housing that is virtually leak proof
- All silver soldered joints ensure electrically and mechanically secure connections

Specifications

Model	VHF Models
Description	NGP Base Loaded 1/2 Wave
Frequency Range	200 - 225 MHz
Center Frequency	Tunable
Gain	2.4 dB
Overall Length	31.5 inches
Whip Style	29 1/2" Straight
Options	Black Chrome Finish Black Shock Spring Shock Spring

[Print](#) [Back](#)