



NOTES

1. MATERIALS:
INSULATOR: GLASS FILLED LCP, 94V-0, COLOR BLACK.
SHIELD: DEEP DRAW STEEL, .020" THICK.
2. PLATING: 150-200 MICRO-INCHES BRIGHT TIN OVER NICKEL OVER COPPER FLASH.
3. CONFORMS TO PRODUCT SPECIFICATION PS-71626.
4. CONFORMS TO APPLICATION SPECIFICATION PS-71624.
5. INSERT MOLDED CONTACT STRIPS ARE SUPPLIED SEPARATELY, SEE SALES DRAWING# SDA-70984-4*** FOR ORDER NUMBERS.
6. BULK PACKAGING: 100 SUB-ASSEMBLIES PER CARTON

B1	ADDED -3001 UDT1999-0661 SCHMIDG 99/02/12
B	REVISED PER ECN U7-0417 SCHMIDG 96/11/08
A	FIRST RELEASE PER ECN# U4-0843 5/27/94 MOS

MFG.	SH.	REV.	LTR.	REVISIONS
------	-----	------	------	-----------

DIMENSIONS SHOWN (METRIC) INCH	
UNLESS OTHERWISE SPECIFIED TOLERANCES: ANGULAR ± 1/2°	
3 PLACE ±	.010
2 PLACE ±	---
1 PLACE	---
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	
DRWG. BY	MOS
CHK'D. BY	DKS
APP'D. BY	GF
SCALE	4: 1

FILE NAME	571624C1
DATE	05/27/94
SHEET NO.	1 OF 1
DATE	05/27/94
TITLE	
160 CKT LFH I/O PLUG HOUSING/SHIELD SUB ASSY. FOR CABLE APPLICATIONS	
MOLEX INCORPORATED	
SEE CHART	
SDA-71624-3000	

71624-3001	WITH M-3 THREADED INSERT
71624-3000	WITHOUT M-3 THREADED INSERT
ITEM NUMBER	DESCRIPTION

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INC. AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.