

| APPLICABLE STANDARD | | | | | |
|--|---|--------------------------|---|--------------------------|----------|
| RATING | OPERATING TEMPERATURE RANGE | -35°C TO 85°C(NOTE 1) | STORAGE TEMPERATURE RANGE | -10°C TO 60°C | |
| | VOLTAGE | 30V AC | APPLICABLE CONNECTOR | BM14C(0.8)-16DS-0.4V(**) | |
| | CURRENT | 0.3A | | | |
| SPECIFICATIONS | | | | | |
| ITEM | TEST METHOD | | REQUIREMENTS | QT | AT |
| CONSTRUCTION | | | | | |
| GENERAL EXAMINATION | VISUALLY AND BY MEASURING INSTRUMENT. | | ACCORDING TO DRAWING. | X | X |
| MARKING | CONFIRMED VISUALLY. | | | X | X |
| ELECTRIC CHARACTERISTICS | | | | | |
| CONTACT RESISTANCE | 20mV AC OR LESS 1kHz,1mA . | | 100mΩ MAX. | X | - |
| INSULATION RESISTANCE | 100V DC. | | 50MΩ MIN. | X | - |
| VOLTAGE PROOF | 100V AC FOR 1 min. | | NO FLASHOVER OR BREAKDOWN. | X | - |
| MECHANICAL CHARACTERISTICS | | | | | |
| MECHANICAL OPERATION | 10TIMES INSERTIONS AND EXTRACTIONS. | | ① CONTACT RESISTANCE: 100mΩ MAX. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS. | X | - |
| VIBRATION | FREQUENCY 10 TO 55 TO 10 Hz,APPROX 5min, SINGLE AMPLITUDE 0.75 mm,10CYCLES, FOR 3 DIRECTIONS. | | ① NO ELECTRICAL DISCONTINUITY OF 1 μs. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS. | X | - |
| SHOCK | 490 m/s ² DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS. | | ① NO ELECTRICAL DISCONTINUITY OF 1 μs. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS. | X | - |
| ENVIRONMENTAL CHARACTERISTICS | | | | | |
| RAPID CHANGE OF TEMPERATURE | TEMPERATURE -55 → +85°C TIME 30 → 30 min UNDER 5 CYCLES. (RELOCATION TIME TO CHANBER : WITHIN 2-3 min) | | ① CONTACT RESISTANCE: 100mΩ MAX. ② INSULATION RESISTANCE: 50MΩ MIN. ③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS. | X | - |
| DAMP HEAT (STEADY STATE) | EXPOSED AT 40 ± 2 °C, 90 TO 95 %, 96 h. | | ① CONTACT RESISTANCE: 100mΩ MAX. ② INSULATION RESISTANCE: 25MΩ MIN. ③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS. | X | - |
| SULPHUR DIOXIDE | EXPOSED IN 25 PPM FOR 96h,25°C,75%. (REFER TO JIS C 60068) | | ① CONTACT RESISTANCE: 100mΩ MAX. ② NO EVIDENCE OF CORROSION WHICH AFFECTS TO OPERATION OF CONNECTOR. | X | - |
| | | | | | |
| | COUNT | DESCRIPTION OF REVISIONS | DESIGNED | CHECKED | DATE |
| | | | | | |
| REMARKS | | | APPROVED | MO. ISHIDA | 16.05.09 |
| NOTE1: INCLUDE THE TEMPERATURE RISING BY CURRENT | | | CHECKED | TS. MIYAZAKI | 16.05.09 |
| Unless otherwise specified, refer to JIS C 5402 and IEC 60512. | | | DESIGNED | NY. YAMASHIRO | 16.05.09 |
| | | | DRAWN | SN. NUMAZAKI | 16.04.28 |
| Note QT:Qualification Test AT:Assurance Test X:Applicable Test | | | DRAWING NO. | ELC-329187-51-00 | |
| | SPECIFICATION SHEET | | PART NO. | BM14C(0.8)-16DP-0.4V(51) | |
| | HIROSE ELECTRIC CO., LTD. | | CODE NO. | CL684-8040-1-51 | 1/1 |