

| APPLICABLE STANDARD | | | | | | |
|--|--|--|-------------------------------------|--|----------|--|
| RATING | OPERATING TEMPERATURE RANGE | -55 °C TO 85 °C | STORAGE TEMPERATURE RANGE | -10 °C TO 50 °C (PACKED CONDITION) | | |
| | VOLTAGE | 30 V AC / DC | OPERATING OR STORAGE HUMIDITY RANGE | RELATIVE HUMIDITY 90 % MAX (NOT DEWED) | | |
| | CURRENT | 0.2 A | APPLICABLE CABLE | t=0.2±0.03mm, GOLD PLATING | | |
| SPECIFICATIONS | | | | | | |
| ITEM | TEST METHOD | REQUIREMENTS | QT | AT | | |
| CONSTRUCTION | | | | | | |
| GENERAL EXAMINATION | VISUALLY AND BY MEASURING INSTRUMENT. | ACCORDING TO DRAWING. | x | x | | |
| MARKING | CONFIRMED VISUALLY. | | x | x | | |
| ELECTRIC CHARACTERISTICS | | | | | | |
| VOLTAGE PROOF | 90 V AC FOR 1 min. | NO FLASHOVER OR BREAKDOWN. | x | x | | |
| INSULATION RESISTANCE | 100 V DC. | 50 MΩ MIN. | x | x | | |
| CONTACT RESISTANCE | AC 20 mV MAX (AC:1 KHz), 1 mA . | 100 mΩ MAX. INCLUDING FPC BULK RESISTANCE (L=12) | x | x | | |
| MECHANICAL CHARACTERISTICS | | | | | | |
| VIBRATION | FREQUENCY 10 TO 55 Hz, HALF AMPLITUDE 0.75 mm, FOR 10 CYCLES IN 3 DIRECTIONS. | ① NO ELECTRICAL DISCONTINUITY OF 1 μs. | x | — | | |
| SHOCK | 981 m/s ² , DURATION OF PULSE 6 ms AT 3 TIMES IN 3 DIRECTIONS. | ② CONTACT RESISTANCE: 100 mΩ MAX. ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS. | x | — | | |
| MECHANICAL OPERATION | 10 TIMES INSERTIONS AND EXTRACTIONS. | ① CONTACT RESISTANCE: 100 mΩ MAX. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS. | x | — | | |
| FPC RETENTION FORCE | MEASURED BY APPLICABLE FPC. (THICKNESS OF FPC SHALL BE t=0.20mm AT INITIAL CONDITION.) | DIRECTION OF INSERTION : 0.15N × NUMBER OF CONTACTS MIN. (note 1) | x | — | | |
| ENVIRONMENTAL CHARACTERISTICS | | | | | | |
| CORROSION SALT MIST | EXPOSED AT 35±2 °C , 5 % SALT WATER SPRAY FOR 96 h. | ① CONTACT RESISTANCE: 100 mΩ MAX. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS. ③ NO EVIDENCE OF CORROSION WHICH AFFECTS TO OPERATION OF CONNECTOR. | x | — | | |
| RAPID CHANGE OF TEMPERATURE | TEMPERATURE-55→+15TO+35→+85→+15TO+35°C TIME 30→ 2 TO 3 → 30→ 2 TO 3 min UNDER 5 CYCLES. | ① CONTACT RESISTANCE: 100 mΩ MAX. ② INSULATION RESISTANCE: 50 MΩ MIN. ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS. | x | — | | |
| DAMP HEAT (STEADY STATE) | EXPOSED AT 40±2 °C, RELATIVE HUMIDITY 90 TO 95 %, 96 h. | | x | — | | |
| DAMP HEAT,CYCLIC | EXPOSED AT -10 TO +65 °C, RELATIVE HUMIDITY 90 TO 96 %, 10 CYCLES,TOTAL 240 h. | ① CONTACT RESISTANCE: 100 mΩ MAX. ② INSULATION RESISTANCE: 1 MΩ MIN. (AT HIGH HUMIDITY) ③ INSULATION RESISTANCE: 50 MΩ MIN. (AT DRY) ④ NO DAMAGE, CRACK AND LOOSENESS OF PARTS. | x | — | | |
| COUNT | DESCRIPTION OF REVISIONS | DESIGNED | CHECKED | DATE | | |
| 0 | | | | | | |
| REMARK | | | APPROVED | RI. TAKAYASU | 09.12.24 | |
| | | | CHECKED | FN. TAMURA | 09.12.24 | |
| | | | DESIGNED | HH. MURAKAMI | 09.12.22 | |
| Unless otherwise specified, refer to JIS C 5402. | | | DRAWN | HK. OSHIKIRI | 09.12.19 | |
| Note QT:Qualification Test AT:Assurance Test X:Applicable Test | | DRAWING NO. | ELC4-158578-06 | | | |
| HRS | SPECIFICATION SHEET | | PART NO. | FH36W-**S-0.3SHW (50) | | |
| | HIROSE ELECTRIC CO., LTD. | | CODE NO. | △ 1/2 | | |

| SPECIFICATIONS | | | | | |
|---|---|--|-------------|------------------------|----------------|
| ITEM | TEST METHOD | REQUIREMENTS | QT | AT | |
| DRY HEAT | EXPOSED AT 85±2 °C, 96 h. | ① CONTACT RESISTANCE: 100 mΩ MAX. | x | — | |
| COLD | EXPOSED AT -55±3°C, 96 h. | ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS. | x | — | |
| SURPHUR DIOXIDE [JIS C 0090] | EXPOSED AT 40±2 °C , RELATIVE HUMIDITY 80 ±5% 25±5 ppm FOR 96 h. | ① CONTACT RESISTANCE: 100 mΩ MAX. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS. | x | — | |
| HYDROGEN SULPHIDE [JIS C 0092] | EXPOSED AT 40±2 °C , RELATIVE HUMIDITY 80±5% , 10 TO 15 ppm FOR 96 h. | ③ NO EVIDENCE OF CORROSION WHICH AFFECTS TO OPERATION OF CONNECTOR. | x | — | |
| SOLDERABILITY | SOLDERED AT SOLDER TEMPERATURE, 235 ±5°C FOR IMMERSION DURATION, 2±0.5 sec. | A NEW UNIFORM COATING OF SOLDER SHALL COVER A MINIMUM OF 95 % OF THE SURFACE BEING IMMersed. | x | — | |
| RESISTANCE TO SOLDERING HEAT | 1) REFLOW SOLDERING : PEAK TMP. 250 °C MAX . REFLOW TMP. OVER 230 °C WITHIN 60 sec. 2) SOLDERING IRONS : TMP. 350 ± 10 °C FOR 5±1 sec . | NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINALS. (note 2) | x | — | |
| <p>(note 1)</p> <p>THIS PRODUCT HAS FLIP-LOCK CONSTRUCTION. FASTEN FPC ON PCB OR SOMETHING FIXED IF FORCE IN VERTICAL DIRECTION SHALL BE PREDICTED.</p> <p>(note 2)</p> <p>BLISTERS WHICH MAY OCCUR IN HOUSING DO NOT AFFECT PRODUCT PERFORMANCE.</p> | | | | | |
| Note QT:Qualification Test AT:Assurance Test X:Applicable Test | | | DRAWING NO. | | ELC4-158578-06 |
| HRS | SPECIFICATION SHEET | | PART NO. | FH36W-**S-0. 3SHW (50) | |
| | HIROSE ELECTRIC CO., LTD. | | CODE NO | △ 2/2 | |