



The 4600 Series Coil Cord is for use with Single-Wire Wrist Straps and SCS Workstation Monitors. Coil Cord features a segmented strain relief and a single bundle of tinsel conductors which provide long cord life and easy movement. Having a 1 megohm current limiting resistor (at the end to attach to the wristband), the Coil Cord meets the resistance requirements of ANSI/ESD S20.20, EIA 625. Alligator clip is included. Made in China.

Specifications	Typical Value
Tensile strength	> 15 lbs. (6.8 kg)
Flex life average	1,000,000 cycles
Resistance end-to-end	1 Megohm $\pm$ 20%
Resistor type	1 Megohm $\pm$ 20%
Plug Size	3.4mm
Plug Type	Straight
Color	Black

Item	Description
<a href="#">4610</a>	Lightweight Coil Cord, 5 ft., 4mm snap
<a href="#">4611</a>	Lightweight Coil Cord, 10 ft., 4mm snap

Unless otherwise noted, tolerance  $\pm$ 10%

Specifications and procedures subject to change without notice.

#### 4610/4611 COIL CORD

926 JR Industrial Drive, Sanford, NC 27332  
WEB SITE: [StaticControl.com](http://StaticControl.com)  
PHONE (919) 718-0000

**DRAWING  
NUMBER**  
4610/4611

**DATE**  
October  
2015

# SCS