

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20

BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL RELEASE	15JUN2015	DL	CW

104
130
27
32
4-Ø4.4
4-M3

45.7

4-Ø4.4
108
130
32
35

开孔安装示意图
PANNEL CUT OUT

NOTES:

1. TECHNICAL CHARACTERISTICS:
 BODY MATERIAL: DIE CAST ALUMINIUM ALLOY
 SURFACE TREATMENT: POWDER-COATED, COLOR SEE TABLE
 OPERATION TEMPERATURE: -40-+125°C
 DEGREE OF PROTECTION: IP65 (MATED)

注释:

1. 技术参数:
 主体材料: 铝合金
 表面处理: 粉末喷涂, 颜色见表格
 工作温度: -40-+125°C
 防护等级: IP65(配合)

SCALE 1:2

139.6
29.8
142.2
(88)

T1430241000-000			-
T1430241000-100	H24B-ADM-BO	GRAY	BODY COATED BOTH INSIDE AND OUTSIDE
T1430241000-200			BODY AND COVER COATED BOTH INSIDE AND OUTSIDE
T1433240000-000		RED	BODY AND COVER COATED, RED
ASSEMBLY PART NUMBER	ASSEMBLY PART DESCRIPTION	COLOR	REMARK

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN 15JUN2015

DAVID LI

CHK 15JUN2015

CHRIS WANG

APVD 15JUN2015

XU XIANG

PRODUCT SPEC

108-137013

APPLICATION SPEC

114-137013

WEIGHT

-

Customer Drawing

TE Connectivity

NAME
H24B-ADM-BO

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A3	-	©-T143X24X000X00	-

SCALE 3:4 SHEET 1 OF 1 REV A

DIMENSIONS:

mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC	±0.1
1 PLC	±0.15
2 PLC	±0.2
3 PLC	±0.25
4 PLC	±0.3
ANGLES	±0.5
FINISH	-

MATERIAL

-

-

1470-19 (3/13)