


断面 A-A SECT



断面 B-B SECT

NOTES

- 1. APPLICABLE HDR HSG: 172520 (25 PITCH)
172890 (20 PITCH)
- 2. PRODUCT SPEC: 108-5163
- 3. CRIMPING SPEC: 114-5062
COMMON APPLICATOR FOR 2/25mm PITCH
HDR HSG = P/M 755765-□
EXCLUSIVE APPLICATOR FOR 25mm PITCH
HDR HSG = P/M 752830-□
- 4. INSTRUCTION SHEET: IS-206J, 207J, 208J

注:

- 1. 適用ヘッド型番 = 172520 (25mmピッチ)
172890 (20mmピッチ)
- 2. 製品規格 = 108-5163
- 3. 取付適用規格 = 114-5062
2/25mmピッチヘッド-ヘッド専用ヘッド型番 = 755765-□
25mmピッチヘッド-ヘッド専用ヘッド型番 = 752830-□
- 4. 取扱説明書 = IS-206J, 207J, 208J

0.95	0.8 ±0.1 DIA, 1.2~1.6	—	POST-TINNED PHOS-BRO. 0.2t 鍍青銅 錫めっき仕上げ 0.2t	172782-9
0.95	0.8 ±0.1 DIA, 1.2~1.6	—	POST TINNED, HIGH HEAT RESISTANCE COPPER ALLOY 高耐熱性銅合金 錫めっき仕上げ 0.2t	1-172782-2
1.2	1 ±0.05 DIA, 1.2~1.6	++	POST-TINNED BRASS 0.2t 鍍黄銅 錫めっき 0.2t	172782-7
0.95	0.8 DIA, 1.2~1.6	—	POST-TINNED BRASS 0.2t 鍍黄銅 錫めっき 0.2t	172782-5
1.2	1 ±0.05 DIA, 1.2~1.6	172798-2	PRE-TURNED BRASS 0.2t 黄銅 0.2t	172782-2
0.95	0.8 DIA, 1.2~1.6	172798-1	黄銅 0.2t	172782-1
A REF	APPLICABLE PCB HOLE AND THK	LOOSE PIECE CONTACT %	MATERIAL	PART NO
参考寸法	適用基板穴径と厚さ	ヘッド端子型番	材料	型番

OBSOLETE

寸法: 単位 DIMENSIONS IN MM. DO NOT SCALE PRINT

PRINT DATE

G1	REVISED PER ECO-11-005030	RK	HMR	EMART
LTR	SEE REVISION RECORD	DR	CHK	DATE

STE TE Connectivity		
WIRE RANGE RANGE 0.2-0.75	WIRE INSULATION DIA. 1.4-1.5	SIZE (NAME) ロ-プロファイルミニ-アンプインコンタクト (LOW PROFILE MINI AMP-IN CONTACT)
MATERIAL 黄銅 (SEE TABLE)	FINISH —	SIZE LOC SIZE (NO) A3 J C-172782
DR. LORNI	DE. M. Oshida	REV. G1 SHEET —
CHK. J. Oshida	APP. J. Oshida	RE (SCALE) 10-1

(CUSTOMER DRAWING) 参考図面