



- MATES WITH RECEPTACLE 207020-1.
- TIN OVER NICKEL PER QQ-N-290.
- GOLD FLASH PER MIL-G-45204 OVER 1.27µm [.000050] MIN NICKEL PER QQ-N-290 ON ENTIRE CONTACT, WITH 0.76µm [.000030] MIN GOLD PER MIL-G-45204 ON ELECTRICAL ENGAGEMENT AREA ONLY.
- ALL CIRCUITS COMMONED TO BUS.
- CONNECTOR IS DIVIDED LENGTHWISE WITH CIRCUITS 1, 2, 5, 6, 9, 10, 13, 14, 17, 18, 21, 22, 25, 26, 29, 30, 33 AND 34 COMMONED, AND CIRCUITS 3, 4, 7, 8, 11, 12, 15, 16, 19, 20, 23, 24, 27, 28, 31, 32, 35 AND 36 COMMONED.
- WILL ACCEPT RING TONGUE TERMINALS, STUD SIZE 10.
- LEAD FREE TIN OVER NICKEL PER QQ-N-290

OBSOLETE	FULL, 36 POSITION	△	△	208063-5
	DUAL, 18 POSITION	△	△	208063-4
	FULL, 36 POSITION	△	△	208063-3
	DUAL, 18 POSITION	△	△	208063-2
	FULL, 36 POSITION	△	△	208063-1
BUS TYPE		CONTACT FINISH		PART NO
THIS DRAWING IS A CONTROLLED DOCUMENT. DWG NO. 06317 09/05/92				
DESIGNED BY: J. MCCLINTON 9-27-92				
DRAWN BY: J. MCCLINTON 9-27-92				
CHECKED BY: J. MCCLINTON 9-27-92				
APPROVED BY: J. MCCLINTON 9-27-92				
SYNOPSIS COMMONING DEVICE ASSEMBLY, 36 POSITION, METRIMATE				
MATERIAL: SEE CALLOUTS		FINISH: SEE CALLOUTS		RESTRICTED TO: --
CUSTOMER DRAWING		SIZE: A1	CAGE CODE: 00779	DRAWING NO: 208063
SCALE: 2:1		SHEET 1 OF 1		REV F