



Mallory Sonalert Products, Inc.

Part #:

SCE048LD2MG7B

Sales Outline Drawing

Revision:

B

Specifications:

Sound Level Category:	Loud	Loud
Mode of Operation:	Continuous	Ding Dong 2.0 - 1.6 kHz
Loudness @ 2 FT:	85 to 95 dB(A) Typ.	85 to 95 dB(A) Typ.
Pulse Rate (PPS):	N/A	1.2
Frequency:	2000 ± 500 Hz	2000 ± 500 Hz
Connection:	T-BLOCK ONLY	T-BLOCK; BLACK WIRE TO (-)
Voltage Rating:	28 to 48 VDC	
Current Draw:	40mA MAX	
Housing Material:	6/6 Nylon, Color: Black	
Storage Temperature:	-40° to +85° C	
Operating Temperature:	-40° to +85° C	
Panel Mounting:	Recommended hole size is 1.25"(31.75mm). Thread front will fit standard 30mm(1.181") hole.	
Knurled Nut:	Used to attach part to panel. The max recommended torque is 10 in-lbs.	
Weight (Typical):	1.6 oz (45g)	
NEMA 3R,4X, & 12:	Approved with use of ACC03.	
cUL Recognition:	Supply voltage shall employ Transient Voltage Surge Suppression.	
Options:	Please contact factory.	

Dimensions: Inches (mm)

cUL Recognized

ROHS Compliant

