


RECOMMENDED MOUNTING HOLE PATTERN Δ
 FOR .063 THICK P.C. BOARD

- Δ POST TO WITHSTAND 13 NEWTONS (3LBS.) MIN. AXIAL FORCE IN BOTH DIRECTIONS SHOWN WITHOUT DISLODGING.
- Δ TOLERANCES APPLY TO SOLDER SIDE OF BOARD.
- Δ MEASURED AT SURFACE \square -A-
- Δ PLASTIC FLASH PERMITTED IN THIS AREA.
- 5 PARTS COMPLY WITH AMP SOLDERABILITY SPEC. NO. 109-11-2.
- Δ ONE HOLE MAY BE UNDERSIZED (.051/.046 DIA.) FOR ASSEMBLY RETENTION DURING WAVE SOLDERING.
- Δ MATERIAL:
 HEADER - THERMOPLASTIC POLYESTER
 GLASS FILLED 94V-0 (NATURAL)
 POST - COPPER ALLOY (TIN PLATED)
- Δ COORDINATE DIMENSION APPLIES FROM CENTER OF ACTUAL FEATURE.
- 9 PLASTIC BURRS CAUSED BY CUT-OFF TOOLING ARE PERMITTED WITHIN THE MAXIMUM TOLERANCE ENVELOPE.
- Δ POST TO BE MEASURED WHEN STRIP IS HELD FLAT.
- Δ POST MUST WITHSTAND TWO 90° BENDS AGAINST EXTRUSION WITHOUT BREAKING.
- Δ DIMENSION SHOULD BE .175 MIN WHEN MATING WITH A MTA-156 CONNECTOR ASSEMBLY OR A SL-156 CONNECTOR ASSEMBLY.
- Δ PIN BURR OF .005 MAX. VERTICAL AND .003 MAX. HORIZONTAL PERMITTED AT POST TIPS ON BOTH ENDS.

.060	1.52	1.560	39.62
.051	1.30	.700	17.78
.046	1.17	.450	11.43
.045	1.14	.425	10.80
.030	0.76	.312	7.92
.016	0.41	.300	7.62
.015	0.38	.180	4.57
.012	0.30	.175	4.45
.010	0.25	.156	3.96
.008	0.20	.125	3.18
.005	0.13	.078	1.98
.003	0.08	.068	1.73
.001	0.03	.063	1.60
[IN]	MM	[IN]	MM

CONVERSION TABLE



THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN: S. HOOVER 07NOV02	Tyco Electronics Corporation Harrisburg, PA 17105-3608	
DIMENSIONS: INCHES		CHK: D. BOSSI 07NOV02	NAME: MTA-.156 HEADER ASSEMBLY, FRICTION LOCK, STRAIGHT .045 ROUND POST, TIN PLATED, 10 POSITION, OMITTED POST	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APRD: D. BOSSI 07NOV02	PRODUCT SPEC: ---	
0 PLC ± -		APPLICATION SPEC: ---		
1 PLC ± -		SIZE: A1		
2 PLC ± -		CAGE CODE: 00779		
3 PLC ± .005		DRAWING NO: 644689		
4 PLC ± -		RESTRICTED TO: ---		
ANGLES ± -		WEIGHT: ---		
FINISH: ---		CUSTOMER DRAWING		
MATERIAL: Δ		SCALE: 5:1		
		SHEET: 1 OF 1		
		REV: D		