

Specification Sheet

Part Number: T150L2X2



Heavy Duty Cable Tie, 32.3" Long, UL Rated, 175lb Tensile Strength, PA66, Red, 25/pkg

Article Number	111-15407
Type	T150L
Color	Red (RD)
Features & Benefits	<ul style="list-style-type: none">• Heavy-duty design offers higher tensile strength.• Buckle feature on head allows excess strap to be tucked away after installation.• Bent tail ensures a quick and simple installation.
Quantity Per	bag

Product Description

Heavy-Duty T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. Durable head design guarantees high tensile strength and a low insertion force. The bent tail allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.

Short Description	Heavy Duty Cable Tie, 32.3" Long, UL Rated, 175lb Tensile Strength, PA66, Red, 25/pkg
Global Part Name	T150L-PA66-RD
Minimum Tensile Strength (Imperial)	175.0
Minimum Tensile Strength (Metric)	780.0
Length L (Imperial)	32.3
Length L (Metric)	820.0
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.35
Width W (Metric)	8.9
Bundle Diameter Min (Imperial)	0.32
Bundle Diameter Min (Metric)	8.0
Bundle Diameter Max (Imperial)	9.6
Bundle Diameter Max (Metric)	243.8

Thickness T (Metric)

1.9

Material

Polyamide 6.6 (PA66)

Material Shortcut

PA66

US MIL SPEC

MIL 53421

Flammability

UL 94 V2

Halogen free

Yes

Operating Temperature (Metric)

-40°F to +185°F (-40°C to +85°C)

ROHS Complaint

Yes

Certification/Specification WEB

UL-ZODZ2.E64139

UL Recognized (US)

Yes

UL Recognized (US and Canada)

Yes

Package Quantity(Imperial)

25

Package Quantity (Metric)

25

Customs Number

3926909987

© 2018 HellermannTyton. All rights reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)