



#### General ordering data

Order No.	8275210000
Part designation	WOS1 5VTTL 50KHZ
Version	WAVE-Series, Optos, 21.6 V DC ... 24 V DC ... 26.4 V DC, 50 mA, Screw connection
EAN	4032248025572
Qty.	1 pc(s).

#### Dimensions

Clamping range, nom.	1.5 mm <sup>2</sup>
Clamping range, min.	0.5 mm <sup>2</sup>
Clamping range, max.	2.5 mm <sup>2</sup>

#### temperature

Ambient temperature (operational)	-25 °C...+60 °C
Storage temperature	-40 °C...+85 °C

#### Approvals

Approvals institutes	CSA; CURUS; GOSTME25; CE
----------------------	--------------------------

#### Control side

Power rating	65 mW
Rated auxiliary voltage	5 V
Rated control voltage	5 V TTL

#### General data

Standards	EN 50178
Humidity	40°C / 93% rel. humidity, no condensation
Conductor connection system	Screw connection
DIN Rail compatibility	TS 35

#### Insulation coordination (EN 50 178)

Clearance and creepage distances for control/load side	≥ 5.5 mm
Overvoltage category	III

#### Insulation coordination (EN 50 178)

Pollution severity	2
Rated impulse withstand voltage	6 kV
Rated voltage	300 V

#### Load side

Protective circuit	Varistor, reverse polarity protection
Rated auxiliary voltage	5 V
Rated switching current	50 mA
Rated switching voltage	21.6 V DC ... 24 V DC ... 26.4 V DC
Short-circuit-proof	No
Status indicator load side	LED green in output
Switch-off delay	7 µs
Switch-on delay	1 µs

#### Classifications

ETIM20	EC001504
ETIM30	EC001504
eClass 4.1	27-27-09-00
eClass 5.0	27-27-09-90
eClass 5.1	27-27-09-90
eClass 6.0	27-27-09-90

#### Similar products

Order No.	Part designation	Version
8275450000	WOS1 12-28VDC 100KHZ	WAVE-Series, Optos, 21.6 V DC ... 24 V DC ... 26.4 V DC, 50 mA, Screw connection