

## Specification Sheet

Part Number: TAG22J-994



Ink Jet Label, Self-Laminating, 1.0" x .5" x 1.63", 32 Per Sheet, PET, White, 1000/pkg

<b>Article Number</b>	593-22994
<b>Type</b>	TAG22J
<b>Color</b>	White (WH)
<b>Features &amp; Benefits</b>	<ul style="list-style-type: none"><li>•HellermannTyton Ink Jet labels are sheet fed for easy loading and fast printing.</li><li>•Ink Jet labels are made with high temperature materials and adhesives so that they will not be affected by the high heat of laser printing.</li><li>•Ink Jet labels are printable using toner for long term UV exposure.</li><li>•Ink Jet labels come in a variety of label sizes and types to fit most applications.</li></ul>
<b>Quantity Per</b>	pack

**Product Description**

HellermannTyton's ink jet self-laminating labels are smear resistant, allowing them to be handled immediately. The labels are made of a heat resistant 1mm polyester film with a strong acrylic based adhesive. The printable area is a special ink-receptive film that absorbs the ink as it is printed on an ink jet printer. Each sheet is smaller than the standard letter size (8.5" x 11".) Less waste results from the smaller sheet size because the user can print smaller quantities at one time. HellermannTyton's ink jet self laminating labels are also more convenient to store.

**Short Description**

Ink Jet Label, Self-Laminating, 1.0" x .5" x 1.63", 32 Per Sheet, PET, White, 1000/pkg

**Global Part Name**

TAG22J-994-WH

**Width W (Imperial)**

1.0

**Width W (Metric)**

25.4

**Bundle Diameter Min (Imperial)**

0.15

**Bundle Diameter Min (Metric)**

3.80

**Bundle Diameter Max (Imperial)**

0.32

**Bundle Diameter Max (Metric)**

8.00

**Thickness T (Metric)**

35.0

**Width of Liner (Metric)**

215.00

**Width of Liner (imperial)**

8.5

**Outside Diameter Max(Imperial)**

0.315

**Outside Diameter Min (metric)**

3.8

**Outside Diameter Min(Imperial)**

0.15

**Outside Diameter Max (metric)**

8.00

**Material**

Type 994, Polyethylene Terephthalate (PET)

**Material Shortcut**

994

**Adhesive**

Acrylic

**Halogen free**

No

**Adhesive Operating Temperature**

-40°F to +302°F (-40°C to +150°C)

**Operating Temperature (Metric)**

-40°F to +302°F (-40°C to +150°C)

**Reach Complaint(Article 33)**

Yes

**ROHS Complaint**

Yes

**Package Quantity(Imperial)**

1000

**Package Quantity (Metric)**

1000

**Customs Number**

3919905060

**Labels per Column**

4

**Labels per Row**

8

**Weight (Metric)**

0.521

**Weight (Imperial)**

1.14