

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

© COPYRIGHT BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.

LOC  
ESDIST  
-

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
B		REVISED PER ECR-10-011717	30MAY2010	S.W	S.Y

RECOMMENDED P.C. BOARD LAYOUT  
P.C. BOARD THK 0.8~1.2  
(VIEW FROM CONNECTOR MOUNTING SIDE)

NOTES

△ MATERIAL HOUSING : THERMOPLASTIC RESIN, UL94V-0  
COLOR ; BLACK

CONTACT : COPPER ALLOY  
RETENTION LEG : COPPER ALLOY

△ FINISH CONTACT : Ni ALL OVER UNDER PL  
Pd-Ni PL. AT CONTACT AREA  
Au FLASH PL. AT CONTACT AREA  
TIN-LEAD PL. AT LEAD AREA  
RETENTION LEG : TIN-LEAD PL.

1612413-1 ; AS SHOWN

A

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN Y.WATANABE 21-JUN-'99  
CHK K.ASAKAWA 21-JUN-'99  
APVD I.ENOMOTO 22-JUN-'99

Tyco Electronics  
Shanghai, P.R.China, 200233

DIMENSIONS:  
MMTOLERANCES UNLESS  
OTHERWISE SPECIFIED:

0-PLG	±	10	±0.2
1-PLG	±	30	>10 ±0.25
2-PLG	±	100	>30 ±0.3
3-PLG	±		
4-PLG	±		
ANGLES			±3°

MATERIAL

△

FINISH

△

PRODUCT SPEC

108-5599

APPLICATION SPEC

WEIGHT

CUSTOMER DRAWING

NAME

PLUG ASSEMBLY  
2.5mm PITCH BATTERY CONNECTOR  
5POS. OFFSET DIP TYPE

SIZE

CAGE CODE

DRAWING NO

RESTRICTED TO

A3

00779

C=1318790

SCALE 2:1

SHEET 1 OF 1

REV B

AMP 1470-19 REV 31MAR2000