

Part Number: 148-90028



Article Number

148-90028

Type

HECP-6

Color

Violet (VT) Clear (CL)

Features & Benefits

- Double Spring Technology for safe, secure and reliable connections
- Low Insertion Forces + High Retention Values
- Accommodates both solid and stranded wire cores
- Polycarbonate Housing for quick visual inspection; Meets UL 92V2 standards
- Low insertion forces reduces buckling of stranded wire
- Able to combine solid and stranded within same housing
- Separate test port for fast, easy confirmation of connection
- Quick Fit Insertion relieves installer in difficult spots like overhead installations, eliminates twisting motion and reduces overall assembly and connection time.
- Max Current Rating to 24 A
- Max Voltage Rating to 600 V (c UL us)

Quantity Per

bag

Product Description

Helacon Plus is a unique push-in wire connector with double spring technology. Double spring design requires less insertion force and delivers superior retention values. Helps alleviate repetitive motion injuries often associated with twist-on style connectors.

Short Description

HelaCon Plus Push-In Style Wire Connector, Double Spring, 6-Port, Polycarbonate, Purple, 250/pkg

Global Part Name

HECP-6-PC-CL/VT

Port Count

6

Length L (Metric)

19.0

Width W (Imperial)

1.12

Width W (Metric)

28.35

Height H (Imperial)

0.41

Height H (Metric)

10.45

Depth D (imperial)

0.75

Depth D (metric)

19.0

Material

Polycarbonate (PC)

Material Shortcut

PC

Flammability

UL 94 V2

Halogenfree

Yes

Operating Temperature Metric

-22°F to +221°F (-30°C to +105°C) -22°F to +230°F (-30°C to +110°C)

ROHS Complaint

Yes

Certification/Specification WEB

NEMKO KEMA-KEUR | EN 60998-2-2:1993 SEMKO DEMKO CEN UL |
ANSI/UL 486-C ENEC VDE | DIN EN 60998-2-2:2005-03 FIMKO UL | ANSI/UL
486-A UL | ANSI/UL 486-B

ULListed (US and Canada)

Yes

Package Quantity(Imperial)

250

Package Quantity (Metric)

50

Customs Number

7413009000

Weight (Imperial)

3.88