



REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
A1	REVISED PER ECO-11-005294	14APR11	HMR

HOUSING	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	PASSIVATE PER ASTM-A380
DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457	N/A
CENTER CONTACT	BERYLLIUM COPPER PER ASTM B 196, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204 OVER NICKEL PLATE PER QQ-N-290
COMPONENT	MATERIAL	FINISH

NOTES:  
 1. CAPTURED CENTER CONTACT  
 2. V.S.W.R.:  
 DC-12.4GHz: 1.06+.005fGHz MAX  
 12.4-18.0GHz: 0.83+.023fGHz

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON FRAC. DEC. ANGLES ± 1/64 ±.005 ± 1°	DRAWN BY SWA	DATE 6/13/85		
	CHECKED BY FN	6/17/85		
	APPD BY D. GORDON	6/18/85	TITLE TYPE N JACK TO SMA JACK ADAPTER	
	USE ASSY PROCEDURE NO. A.P. N/A		SIZE B	CODE IDENT NO. 26805
	CUSTOMER DRAWING	SCALE 5=1	1057343-1	REV A1
			SHEET 1 OF 1	