



ULD-300 Ultrasonic Leak Detector

When leaks occur they often generate an ultrasonic frequency that is beyond human hearing. Amprobe's TMULD-300 converts these sounds into an audible range for easy detection. The TMULD-300 tests pressurized air lines, refrigeration systems, steam lines for leaks. Quickly and easily locate a leak location with this unique device.

- Locates arcing in an electrical system
- Useful in finding the ends of buried PVC pipes
- Includes Parabola shield to reduce background noise, extension tube to access difficult or dangerous areas

No hassle warranty

No waiting.

No shipping charges.



Our commitment to high-quality products and customer service is demonstrated by our industry exclusive "No Hassle" warranty. In the unlikely event that an Amprobe Test Tool requires warranty service, any of our local dealers are authorized to replace it, on the spot.

(note: \$500 MSLP limit)



ULD-300 Ultrasonic Leak Detector

Data Sheet

Specifications

General Specifications	
Operating Temperature	0°C to 38°C (32°F to 100°F)
Storage Temperature	-40°C to 66°C (-40°F to 150°F)
Weight	180 Grams (6.3 Ounces) with Battery
Dimensions	185.4 x 63.5 x 25.4 mm (7.3 x 2.5 x 1 in.)
Frequency Response	35 kHz to 45 kHz + 6 db
Power Consumption	22 mA at 9 Volts DC
Battery Life	33 Hours with 9 Volt Alkaline Battery (NEDA 1604A, IEC 6LR61)
Performance	Meets the ASTM Standard: ASTM E1211-07
Battery Test	LED Color indicator: Green-Good; Red-Replace
Case	High Impact ABS Plastic



Included Parts

Part Number	Description
TEA-1	Flexible Tubing Adapter
TE-2	Tubular Extension
ULD-CC	Carrying Case
PB-1	Parabola
HP-1	Headphones

Amprobe® Test Tools
website: www.Amprobe.com
email: info@amprobe.com
Everett, WA 98203
Tel: 877-AMPROBE

Amprobe® Test Tools Europe
Amprobe Test Tools Europe
Beha-Amprobe GmbH
In den Engematten 14
79286 Glottertal, Germany
Tel.: +49 (0) 7684 8009 - 0

©2009 Amprobe Test Tools. All rights reserved.
03/2009 3465265 Rev A