



Smart Technology. Delivered.



# Vehicular 4-Port MIMO Antenna

## VLQ69273x22N

**698-960 / 1710-2700 / 2300-2700 / 4900-5900 MHz**

The Laird vehicular 4-port MIMO antenna covers the 698-960 / 1710-2700 MHz, 2300-2700 / 4900-5900 MHz. The VLQ69273x22N is configured with 4-port, dual-band elements.

Connector options include SMA male connectors for 3G/4G LTE with RSMA male connectors for the WiFi port. The housing incorporates a low-profile, rugged design that meets IP67 standards. The antenna also features high impact, UV-resistant polycarbonate plastic available in black or white.

### SPECIFICATIONS

PARAMETER	PERFORMANCE			
Model Number	VLQ69273B22N-518A (Black)		VLQ69273W22N-518A (White)	
No. of Ports	4 (2-ports 3G/4G LTE, 2-ports WiFi)			
	3G/4G (LTE) Ports		WiFi Ports	
Frequency Bands (MHz)	698-960 MHz	1710-2700 MHz	2300-2700 MHz	4900-5900 MHz
Peak Gain * dBi	3.2	4.5	5.5	6.3
Max Gain +/- 30° above horizon	N/A	N/A	N/A	4.8
VSWR* Typical	< 1.8:1	< 1.9:1	< 2.0:1	< 1.6:1
VSWR* Max	< 2.0:1	< 2.0:1	< 2.0:1	< 2.0:1
Typical Port-to-Port Isolation *	698-960	1710-2700	2300-2700	4900-5900
LTE1-to-LTE2	> 14 dB	> 20 dB	> 23dB	N/A
LTE1-to-WiFi	> 23 dB	> 20 dB	> 20 dB	> 40 dB
LTE2-to-WiFi	> 23 dB	> 20 dB	> 20 dB	> 38 dB
LTE1-to-LTE2	> 25 dB	> 19 dB	> 20 dB	> 36 dB
LTE1-to-WiFi	> 23 dB	> 20 dB	> 21 dB	> 39 dB
LTE2-to-WiFi	N/A	N/A	> 20 dB	> 26 dB
Nominal Impedance	50 Ω			
Polarization	Vertical Linear			
Azimuth Beam Width	Omnidirectional			
Input Power, Max	50 Watt (ambient temp. of 25°C / 77°F)			
Operating Temperature	-30°C - +70°C (-22°F to +158°F)			
Dimensions (dia. x hgt)	132 mm x 75 mm (5.2" x 2.9")			
Weight	Approximately 1.04 kg (2.29 lbs)			
Connector	SMA-Male (3G/4G LTE port)		RSMA-Male (WiFi port)	
Cable (exposed length)	LMR195M- 518.2 cm (17 ft)			
Radome / Baseplate Material	PC, UL94 - V0 Rating, UV Stable			
Material Compliance	ROHS compliant			
IP Dust & Water Ingress Rating	IP67			

\*Measured on 1 ft. (30.48 cm) diameter ground plane

### PART NUMBERS

#### PART NUMBER

VLQ69273B22N-518A 2-Ports 4G/LTE: SMA Male; 2 Ports WiFi:RSMA Male(Black)

VLQ69273W22N-518A 2-Ports 4G/LTE: SMA Male; 2 Ports WiFi:RSMA Male(White)

Americas: +1.847.839.6907  
IAS-AmericasEastSales@lairdtech.com

Europe: +44.1628.858941  
IAS-EUSales@lairdtech.com

Asia: +86.21.5855.0827.127  
IAS-AsiaSales@lairdtech.com

[www.lairdtech.com](http://www.lairdtech.com)

Laird warrants to the original end user customer of its products that its products are free from defects in material and workmanship. Subject to conditions and limitations Laird will, at its option, either repair or replace any part of its products that prove defective by reason of improper workmanship or materials. This limited warranty is in force for the useful lifetime of the original end product into which the Laird product is installed. Useful lifetime of the original end product may vary but is not to exceed five (5) years from the original date of the end product purchase.



ANT-DS-VLQ69273x22N 0815

Any information furnished by Laird Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird materials rests with the end user, since Laird and its agents cannot be aware of all potential uses. Laird makes no warranties as to the fitness, merchantability or suitability of any Laird materials or products for any specific or general uses. Laird shall not be liable for incidental or consequential damages of any kind. All Laird products are sold pursuant to the Laird Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2015 Laird Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Logo, and other marks are trade marks or registered trade marks of Laird Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird or any third party intellectual property rights.