

Device connector, front mounting - RC-12P1N122300 - 1596903

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Device connector for front wall, straight, shielded: yes, Screw locking, M23, Number of positions: 12, Type of contact: Male connector, Solder connection, Flat gasket, 4x Ø3.2



Key Commercial Data

Packing unit	1 STK
Weight per Piece (excluding packing)	29.740 g
Custom tariff number	85366990
Country of origin	Germany


Technical data

Product type	Circular connectors (device side)
Approval	EAC
Number of positions	12
Coding	N
Type	Device connector for front wall
Mounting type	4x Ø3.2
Rated current (IEC)	8
Rated voltage (IEC)	150
Thread	M23
Shielding	yes
Signal type	Signal

Drawings

Device connector, front mounting - RC-12P1N122300 - 1596903

Schematic diagram



Classifications

eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701
eCl@ss 6.0	27260708
eCl@ss 7.0	27440312
eCl@ss 8.0	27440103
eCl@ss 9.0	27440102

ETIM

ETIM 3.0	EC001121
ETIM 4.0	EC001121
ETIM 5.0	EC002641

UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	43172015
UNSPSC 12.01	43201404
UNSPSC 13.2	43201404

Approvals

Approvals

Approvals

EAC

Ex Approvals

Device connector, front mounting - RC-12P1N122300 - 1596903

Approvals

Approval details

EAC B.01742
