



Datasheet for part number CIR06F-36-5SY-F80

|   |
|---|
| Our Catalog Part Number: CIR06F-36-5SY-F80  |
| Brand: VEAM Product Category: Circular Product Line: Veam CIR, VBN, Other Series: CIR / FRCIR |

|  |  |
|--|--|
| Product Datasheet                                  |  |
| SERIES   | Connector with Bayonet Coupling  |
| Shell Style  | Straight Plug Connector  |
| Environmental Class                                | Backshell with A style clamp and bushing but includes wire sealing grommet and compression ring.   |
| Shell Size   | 36   |
| Contact Arrangement                                | 36-5   |
| Total Number of contacts                           | 4 contacts   |
| Number of Contacts Size 0                          | 4 contacts size 0  |
| Insulator Rotation                                 | 240°   |
| Gender   | Socket   |
| Contact Type                                       | Crimp for AWG wire (used in F80 insert)  |
| Contact Plating                                    | Silver   |
| Shell Material                                     | Aluminium alloy  |
| Shell Plating                                      | Olive drab chromate over cadmium plating (conductive)  |
| Wire Size Cross Section for Contacts Size 0        | 53 mm <sup>2</sup> or AWG 0  |
| Contact Rating for Contacts Size 0                 | Maximum Current = 245 A<br>Rated and Test Current = 150 A<br>Potential Drop max. 53 mV   |
| Shock Resistance                                   | Waterproof to 10 meters (33 ft)<br>12 h (14.7 PSI)   |
| Coupling   | 2000 couplings minimum   |
| Service Rating Letter                              | A  |
| Operating Voltage DC                               | 700 V  |
| Operating Voltage AC                               | 500 V  |
| Dielectric strength - Minimum Flashover AC RMS     | 2800 V   |
| Dielectric strength - Test Voltage AC RMS (Hi Pot) | 2000 V   |
| Note   | Voltages in excess of 30 V ac or 42.5 V dc are potentially hazardous and care should be taken to ensure that such voltages can't be transmitted in any way to exposed metal parts of the connector body. |
| General  | Veam CIR series Connectors are produced in accordance with NATO Standard VG95234, which is based on MIL-C-5015 for physical size, layout and environment requirements.                                   |