



REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
01 ₂	SEE ECN 80-0084	VM 2/22/80	BZ 2/28/80
01 ₃	REDRAWN ON CAD, ECN 92-0010	<i>OKR</i> 07/09/92	<i>M.M.</i> 07/14/92
01 ₄	REVISED PER ECN 99-0094	DM 7/16/99	<i>S. Mady</i>

DESIGNED FOR USE WITH .141 DIA S.R. CABLE CABLE ENTRY DIAMETER MINIMUM	
HOUSING	.144
CONTACT	.037

ELECTRICAL	MECHANICAL	ENVIRONMENTAL	HOUSING	DIELECTRIC	CENTER CONTACT	COMPONENT	MATERIAL	FINISH
Nominal Impedance (Ohms) <u>50</u>	Interface Dimensions MIL-STD-348A, Fig. 310.2	Temperature Rating <u>-65°C to +125°C</u>	STAINLESS STEEL PER ASTM-A484 AND ASTM- A582, TYPE 303	PTFE FLUOROCARBON PER ASTM-D-1457	BERYLLIUM COPPER PER ASTM B 196, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204		
Frequency Range (GHz) DC to <u>18</u>	Recommended Mating Torque <u>N/A</u>	Vibration MIL-STD-202, Method 204, Condition D				N/A		
Volt Rating (VRMS MAX) @ Sea Level <u>500</u>	Mating Characteristics: Insertion (MAX Lbs) <u>3</u>	Shock MIL-STD-202, Method 213, Condition I						
VSWR <u>1.05 + .005 f(GHz)</u>	Withdrawal (MIN Oz) <u>1</u>	Thermal Shock MIL-STD-202, Method 107, Condition B, Except High Temp 115°C						
Insertion Loss (dB MAX) <u>.03 √f(GHz)</u>	Force to Engage and Disengage (In-Lbs MAX) <u>2</u>	Moisture Resistance MIL-STD-202, Method 106						
RF Leakage (dB MIN) <u>-[90-{f(GHz)}]</u>	Center Contact Captivation Axial (Lbs) <u>N/A</u>	Corrosion - MIL-STD-202, Method 101, Condition B, 5% salt spray						
Corona, 70,000 Ft (VRMS MIN) <u>375</u>	Radial (In-Oz) <u>N/A</u>							
Dielectric Withstanding Voltage (VRMS MIN) @ Sea Level <u>1,500</u>	Cable Retention Axial Force (Lbs) <u>60 Min</u>							
Contact Resistance (Milliohms MAX) Center Contact <u>2.0</u>	Torque (In-Oz) <u>55 Min</u>							
Outer Contact <u>2.0</u>	Weight (Grams) <u>TBD</u>							
Cable to Housing <u>0.5</u>								
RF High Potential @ Sea Level (VRMS MIN @ 5 MHz) <u>1,000</u>								
LR.(Megohms MIN) <u>5,000</u>								

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES
TOLERANCE ON
FRAC. DEC. ANGLES
± 1/64 ±.005 ± °

These drawings and specifications are the property of AMP Incorporated and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.

DRAWN BY BWC DATE 6/5/67
CHECKED BY ED 8/19/67
APPD BY D.NANIA 8/31/67

USE ASS'Y PROCEDURE
408-04767
NO. AP. (20-009)

AMP Incorporated
140 Fourth Avenue
Waltham, MA 02451-7599

AMP

TITLE OSM 4-HOLE FLANGE MOUNT
CABLE JACK
DIRECT SOLDER ATTACHMENT

SIZE <u>B</u>	CODE IDENT NO. <u>26805</u>	<u>2006-7941-00</u>	REV <u>01₄</u>
SCALE <u>4:1</u>		SHEET <u>1</u> OF <u>1</u>	