

## Specification Sheet

Part Number: 111-12301



Wide-Strap Cable Tie, 12.1"L, 0.375"–3.25" Bndl Dia, 120lb Tens Stngth, PA66HIRHSUV, Black, 300/pkg

Article Number	111-12301
Type	WSI
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none"><li>•Wide strap is designed to minimize pinching of soft hoses and convoluted tubing.</li><li>•Low-profile head with clamping rails provide compact bundling with a full circumferential compression around bundles.</li><li>•Wider and thinner strap design increases flexibility, provides low insertion and minimizes pinching of bundles.</li><li>•Bent tail allows for quick insertion into head or mounts.</li></ul>
Quantity Per	bag

### Product Description

The Heavy Duty Wide-Strap Cable Tie was designed to minimize the pinching of soft bundles and the potential of lateral movement along the bundle. The low-profile head and underside clamping rails increase the grip around the bundle and provide a better fit than traditional cable ties. These are used primarily in the trucking and heavy equipment industries, but can be used in a wide variety of applications where strength is needed.

**Short Description**

Wide-Strap Cable Tie, 12.1"L, 0.375"-3.25" Bndl Dia, 120lb Tens Stngth, PA66HIRHSUV, Black, 300/pkg

**Global Part Name**

WSI-PA66HIRHSUV-BK

**Minimum Tensile Strength (Imperial)**

120

**Minimum Tensile Strength (Metric)**

535

**Length L (Imperial)**

12.1

**Length L (Metric)**

307.0

**Identification Plate Position**

none

**Releasable Closure**

No

**Tie Closure**

plastic pawl

**Variant**

Inside Serrated

**Width W (Imperial)**

0.5

**Width W (Metric)**

12.7

**Bundle Diameter Min (Imperial)**

0.375

**Bundle Diameter Min (Metric)**

9.7

**Bundle Diameter Max (Imperial)**

3.2

**Bundle Diameter Max (Metric)**

83.8

**Thickness T (Imperial)**

0.055

**Thickness T (Metric)**

1.4

**Cable Tie Head Length (Imperial)**

0.393

**Cable Tie Head Width (Imperial)**

0.78

**Material**

Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

**Material Shortcut**

PA66HIRHSUV

**Flammability**

UL 94 HB

**Operating Temperature (Metric)**

-40°F to +230°F (-40°C to +110°C)

**Reach Complaint(Article 33)**

Yes

**ROHS Complaint**

Yes

**Package Quantity(Imperial)**

300

**Package Quantity (Metric)**

300

**Customs Number**

3926909987

**Content Unit(BMEcat)**

pcs.

**Weight (Metric)**

0.0055

**Weight (Imperial)**

0.0121

---

© 2018 HellermannTyton. All rights reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)