

Aug.1.2018 Copyright 2018 HIROSE ELECTRIC CO., LTD. All Rights Reserved.  
 In case that the application demands a high level of reliability, such as automotive,  
 please contact a company representative for further information.

APPLICABLE STANDARD		MIL-C-5015				
RATING	OPERATING TEMPERATURE RANGE	-40 °C TO +125 °C		STORAGE TEMPERATURE RANGE	-10 °C TO +60 °C	
	VOLTAGE	AC 500 V , DC 700 V				
	CURRENT	13 A <sup>(1)</sup>		APPLICABLE CABLE		
<b>SPECIFICATIONS</b>						
ITEM	TEST METHOD			REQUIREMENTS	QT	AT
<b>CONSTRUCTION</b>						
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.			ACCORDING TO DRAWING.	X	X
MARKING	CONFIRMED VISUALLY.				X	X
<b>ELECTRIC CHARACTERISTICS</b>						
CONTACT RESISTANCE	CONTACT SHALL BE MEASURED AT DC 1 A. (MIL-C-2316)			5 mΩ MAX.	X	X
INSULATION RESISTANCE	500 V DC. (MIL-STD-1344 3003)			5000 MΩ MIN.	X	X
VOLTAGE PROOF	1000 V AC. FOR 1 min. (MIL-STD-1344 3001)			NO FLASHOVER OR BREAKDOWN.	X	X
<b>MECHANICAL CHARACTERISTICS</b>						
CONTACT INSERTION AND WITHDRAWAL FORCES	φ1.562 <sub>0</sub> <sup>+0.003</sup> BY STEEL GAUGE.			INSERTION AND WITHDRAWAL FORCES : 0.6 N MIN.	X	-
CONNECTOR INSERTION AND WITHDRAWAL FORCES	MEASURED BY APPLICABLE CONNECTOR. (WITHOUT LOCK MECHANISM)			INSERTION AND WITHDRAWAL FORCES : 30 N MAX.	X	-
MECHANICAL OPERATION	500 TIMES INSERTIONS AND EXTRACTIONS. (MIL-C-5015 4, 6, 12, 2)			CONTACT RESISTANCE: 7.5 mΩ MAX.	X	-
VIBRATION	FREQUENCY: 10 TO 500 Hz, SINGLE AMPLITUDE 0.75 mm, 98 m/s <sup>2</sup> AT 3h, FOR 3 DIRECTIONS. (MIL-STD-1344 2005, CONDITION II)			① NO ELECTRICAL DISCONTINUITY OF 10 μs. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X	-
SHOCK	490 m/s <sup>2</sup> DURATIONS OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS. (MIL-STD-1344 2004, CONDITION E)			① NO ELECTRICAL DISCONTINUITY OF 10 μs. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X	-
<b>ENVIRONMENTAL CHARACTERISTICS</b>						
DAMP HEAT (STEADY STATE)	EXPOSED AT 71°C, 95%, 336h. (MIL-C-5015 4, 6, 10)			① INSULATION RESISTANCE: 50 MΩ MIN. (AT HIGH HUMIDITY). ② INSULATION RESISTANCE: 500 MΩ MIN. (AT DRY). ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X	-
RAPID CHANGE OF TEMPERATURE	TEMPERATURE -55 → R/T <sup>(2)</sup> → +125 → R/T °C TIME 30 → 10 TO 15 → 30 → 10 TO 15 min UNDER 5 CYCLES. (MIL-C-5015 4, 6, 4)			① INSULATION RESISTANCE: 5000 MΩ MIN. . ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X	-
SEALING <sup>(3)</sup>	EXPOSED AT A DEPTH OF 1.8 m FOR 48 h.			NO WATER PENETRATION INSIDE CONNECTOR.	X	-
AIRTIGHTNESS <sup>(3)</sup>	APPLY AIR PRESSURE 40 kPa FOR 30 s TO INSIDE CONNECTOR.			NO AIR BUBBLES FROM CONNECTOR INTERFACE.	X	-
RESISTANCE TO SOLDERING HEAT	SOLDERED AT SOLDER TEMPERATURE, +380°C±10°C FOR SOLDERING DURATION, 5±1 s.			NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINALS.	X	-
SOLDERABILITY	SOLDERED AT SOLDER TEMPERATURE, +350°C±10°C FOR SOLDERING DURATION, 5±1 s.			WETTING ON SOLDER SURFACE. NO SOLDER CLUSTER.	X	-
CORROSION SALT MIST	EXPOSED IN 5 % SALT WATER SPRAY FOR 48 h. (MIL-STD-1344 1001 CONDITION B)			NO HEAVY CORROSION RUIN THE FUNCTION.	X	-
OIL RESISTING <sup>(3)</sup>	DROP CUTTING OIL FOR 48 HOURS AT THE RATE OF 0.5 L/h. (JIS B 6015)			NO OIL SEEPAGE INSIDE CONNECTOR.	X	-
	COUNT	DESCRIPTION OF REVISIONS		DESIGNED	CHECKED	DATE
Q						
REMARK				APPROVED	SU. OBARA	10.10.12
NOTES (1) 13 A RATED CURRENT IS THE MAXIMUM CURRENT FLOW PER CONTACT. BUT THE CURRENT CAPACITY OF WHOLE IS CONNECTOR 24.5 A MAX. . (2) R/T : ROOM TEMPERATURE (3) SEALING AND AIRTIGHTNESS SHALL BE TESTED BY APPLICABLE CONNECTOR.				CHECKED	HY. KISHI	10.10.12
				DESIGNED	TH. KAMEYA	10.10.12
				DRAWN	YS. SAKODA	10.10.07
Unless otherwise specified, refer to JIS C 5402.						
Note QT:Qualification Test AT:Assurance Test X:Applicable Test				DRAWING NO.		ELC4-044047-73
<b>HRS</b>	SPECIFICATION SHEET			PART NO.	H/MS3106A10SL-4S (73)	
	HIROSE ELECTRIC CO., LTD.			CODE NO.	CL120-0601-3-73	△ 1/1