

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © COPYRIGHT - By - ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS			
P	LTR	DESCRIPTION	DATE	DWN	APVD
GP	00	B	REVISED PER ECO-11-006475	20OCT2011	CJV CWR

- 1 RECEPTACLE ACCEPTS SIZE 22 DF SOCKET CONTACTS. CONTACTS MUST BE PURCHASED SEPARATELY.
- 2 ALL PARTS SHIPPED UNASSEMBLED.
- 3 FLAME RETARDANT 94V-0 RATED, STYRENE POLYOLEFIN OR PVC, BLACK.
- 4 FLAME RETARDANT 94V-0 RATED, GLASS FILLED NYLON OR POLYESTER, BLACK.
- 5 STEEL PER ASTM A109.
- 6 TIN PLATING PER MIL-T-10727.
- 7 ELECTRODEPOSITED POLYURETHANE, BLACK.
- 8 COMPONENTS INDIVIDUALLY BULK PACKED.
- 9 ZINC ALLOY.

EXPANDING NECK, ACCOMMODATES CABLE FROM .190-.375 DIA

1.685 MAX

FERRULE, MUST BE PURCHASED SEPARATELY, AS REQUIRED BY CABLE DIAMETER

4-40 JACKSCREW QTY: 2

SHIELD QTY: 2

ENCLOSURE

RCPT CONNECTOR HDP-22

1.467 TYP

.812 TYP

1.630 MAX

CABLE REF

.125 MAX

1.640 MAX

1.312 ± .005

W/ LOGOS	8	1658689-1
REMARKS	PACKAGING	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	13AUG07	TE Connectivity	
DIMENSIONS: INCHES		CHK	13AUG07	SHIELDING ENCLOSURE KIT, RCPT, SIZE 2, 26 POSN, HDP-22, AMPLIMITE	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD	13AUG07	SIZE	CAGE CODE
0 PLC	± -	NAME		DRAWING NO	RESTRICTED TO
1 PLC	± -	PRODUCT SPEC		SCALE	SHEET
2 PLC	± -	APPLICATION SPEC		2:1	1 of 1
3 PLC	± .020	WEIGHT		REV	B
4 PLC	± -	CUSTOMER DRAWING			
ANGLES	± -	A2 00779 C=1658689			
FINISH	6 7				

1471-9 (3/11)

1658689

A