

## FO connectors - FOC-V14-C1ZNI-S/SJFH:10 - 1408048

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Push-pull connector (version 14), die-cast zinc, with SC-RJ insert for PCF, for cable diameter of 5.5 mm ... 10 mm, cable outlet at the top

### Product Features

- Push-pull ADVANCE connector
- Locking system to prevent inadvertent removal
- Highest ESD and EMC resistance for reliable transmission



### Key Commercial Data

Packing unit	1 pc
Custom tariff number	85367000
Country of origin	Germany

### Technical data

#### Standards and Regulations

Standards/regulations	IEC PAS 61076-3-117
-----------------------	---------------------

### Classifications

eCl@ss

eCl@ss 4.0	27140816
eCl@ss 4.1	27140816
eCl@ss 5.0	27189239
eCl@ss 5.1	27189239
eCl@ss 6.0	27144001
eCl@ss 7.0	27144001
eCl@ss 8.0	19170122

## FO connectors - FOC-V14-C1ZNI-S/SJFH:10 - 1408048

### Classifications

#### ETIM

ETIM 3.0	EC000007
ETIM 4.0	EC000489
ETIM 5.0	EC001122

#### UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501

### Drawings

Dimensional drawing

