



- 1 0.00076[.000030] MINIMUM GOLD IN CONTACT AREA, 0.00381[.000150] MIN TIN-LEAD ON SOLDER TAILS, ALL OVER 0.00127[.000050] MINIMUM NICKEL
- 2. CUSTOMER TO PROVIDE CARD GUIDANCE SYSTEM
- 3 DATUMS AND BASIC DIMENSIONS ESTABLISHED BY CUSTOMER
- 4. CONNECTOR REQUIRES USE OF 2 - SIZE 2M SCREWS FOR FASTENING TO PRINTED CIRCUIT BOARD
- 5 ASSEMBLY KEYED FOR 5 VOLT CARDS
- 6 ASSEMBLY KEYED FOR LOW VOLT CARDS (3.3V)
- 7 RECESSED AMP AND CSA LOGOS LOCATED ON BOTH SIDES OF HOUSING.
- 8 MATERIAL: HOUSING & ORGANIZER; LCP, COLOR; BLACK PIN; BRASS

VOLTAGE KEYING & IDENTIFICATION	1,17,34	ALL OTHER PINS	36,67	535653-2
	35,51,68	ALL OTHER PINS	36,67	535653-1
	5.0	4.25	3.5	
	[.197]	[.167]	[.138]	
"L" (PIN LENGTH) AND LOCATION				PART NO.
THIS DRAWING IS A CONTROLLED DOCUMENT.				
DWN J. MOSER 3/8/93		Tyco Electronics Corporation		
CHK B. ELICKER 3/8/93		Harrisburg, PA 17105-3608		
APVD		NAME		
DIMENSIONS:		PRODUCT SPEC		
INCHES		APPLICATION SPEC		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		SIZE CAGE CODE DRAWING NO RESTRICTED TO		
0 PLC ± -	1 PLC ± -	WEIGHT 7.3 GRAMS		
2 PLC ± 0.13 [.005]	3 PLC ± -	A1 00779 C=535653		
4 PLC ± -	5 PLC ± -	CUSTOMER DRAWING		
ANGLES FINISH		SCALE 4:1 SHEET 1 OF 1 REV F		