


NO.	MASSE / DIMENSION
A	62.8
B	2 1/4-16UN-2B
C	35.7
D	2-18NS-2A
E	11.8
F	64

NO.	BESCHREIBUNG / DESCRIPTION
1	ISOLIERKÖRPER STIFT / INSULATOR PIN
3	DICHTKÖRPER / GROMMET
4	ENDRING / ENDRING
5	KONTAKTSTIFT/ CONTACT PIN
7	ZYLINDERGHÄUSE / BARREL
9	ÜBERWURFMUTTER / COUPLING NUT
14	F-ENDGEHÄUSE / F-ENDBELL



Note: Due to an automatic nomenclature system, numbers generated may not be sequential.
 Specification and Dimensions subject to change
 Drawings illustrate normal insulator positioning

Material Specification:	
Shell Material:	Aluminium alloy
Shell Plating:	Olive drab chromate coating over cadmium plating
Insulator Material:	Neoprene
Contact Material:	Copper alloy
Contact Plating:	Hard silver

all dimensions are in mm
 Dimensions without tolerance indications are general tolerances in acc. with DIN7168m

drawing for
 CUSTOMER



description CA3106F36-15P-F80
 Plug, straight
 Endbell for flex tube
 AWG Crimp / Pin / Layout: 36-15

© All rights reserved. Reproduction or issue to third in any form whatever is only permitted with written authorization of ITT Cannon
 page 1/1
 revision 769 16. Jul 18