



BCM5714C PRODUCT Brief



PCI EXPRESS®-TO-PCI-X® I/O BRIDGE WITH INTEGRATED DUAL GIGABIT ETHERNET PORTS

FEATURES

- Dual Gigabit Ethernet (GbE)
- PCI Express®-to-PCI-X® bridge
- Dual integrated 10BASE-T/100BASE-TX/1000/BASE-T BCM5714C transceivers
- Dual 10/100/1000 trispeed media access controllers (MACs)
- MACs
 - Integrated high-speed RISC cores
 - 56 KB receive and 22 KB transmit buffers
 - CPU task offload features (TCP, IP, UDP checksum, and Microsoft® Large Send Offload)
- TCP segmentation, IP fragmentation, and reassembly
- Robust manageability
 - Preboot execution environment (PXE) 2.0 remote boot
 - Universal Management Port interface for high-speed system management traffic
 - IPMI-compliant server management interface
 - Out-of-Box Wake-on-LAN (OoB WOL)
 - Statistic gathering (SNMP MIB II, Ethernet-like MIB, Ethernet MIB) for 802.3x, clause 30
 - Comprehensive diagnostic and configuration software suite
 - SMBus 2.0 controller
- Power management, ACPI 1.1a-compliant in multiple power modes

FEATURES (CONT.)


- Advanced features
 - Priority queuing—802.1p Layer 2 priority encoding
 - Virtual LANs—802.1q VLAN tagging and support for up to 64 VLANs
 - Jumbo frames (9 KB)
 - 802.3x flow control
 - Link aggregation—802.3ad, GEC/FEC, and Smart Load Balancing™
 - Failover
- Performance features
 - CPU task offload
 - Adaptive interrupts
 - PCI-X split transaction
 - Configurable, non-symmetric host interface access
- 484-pin PBGA package
- Power
 - Rails—1.2V core, 2.5V I/O, and 3.3V I/O
 - Peak power dissipation of 5.4W
 - Average power dissipation of 4.6W

APPLICATIONS

- Highly integrated LAN on Motherboard (LOM) designs
- Blade servers
- Rack-optimized servers



OVERVIEW



System Block Diagram

The BCM5714C device is a highly integrated communication and storage bridge for entry-level servers and embedded applications. The primary applications of the BCM5714C are UP and DP servers featuring PCI Express connectivity for I/O expansion.

The BCM5714C provides these key features:

- Dual gigabit NIC ports (MAC and PHY)
- One full 64-bit/133 MHz PCI-X 1.0 bus
- Host interface of PCI Express

The BCM5714C connects to server chip sets with an x4 PCI Express interface and provides an independent PCI-X 1.0 bus for peripheral connectivity. The x4 PCI Express interface is a flexible design and supports x1 and x2 PCI Express connectivity as well. The PCI-X bus is 64 bits wide and runs at 133 MHz.

As an integrated I/O bridge that provides a high-performance data flow path between the PCI Express host interface and the integrated I/O subsystem, the PCI-X bus provides high-performance I/O expansion within the system, while the Gigabit Ethernet interfaces provide high performance network interfaces to the external world. The 64-bit PCI-X bus segment operates at 33 MHz, 66 MHz, 100 MHz, and 133 MHz. The GbE interface represents the fourth generation of Broadcom® server controllers with fully integrated copper transceivers.

The features of the PCI-X bridge include the following:

- Allow concurrency between the PCI Express and the PCI-X buses

- Eight-deep PCI Express-to-PCI-X memory write posting (PCI Express-to-PCI-X transactions)
- Four-deep PCI Express-to-PCI-X non-posted request queue (PCI Express-to-PCI-X transactions)
- Caching with a 16-deep, 32-byte I/O cache for PCI-to-main memory transactions for each PCI bus
- Support write-through caching protocol
- Support up to 14 outstanding split transactions (PCI-X-to-main memory transactions)
- Eight-deep PCI-X-to-PCI Express request queue (PCI-X-to-main memory transactions)
- Parity protection on the PCI-X bus in a conventional PCI and PCI-X mode1
- Optional ECC protection on the PCI-X bus in PCI-X mode1
- Three programmable regions each for PCI-X memory and one region for I/O
- VGA-compatible addressing support
- Multiple I/O APIC support
- Peer-to-peer transfer support
- Integrated PCI-X bus arbitration that supports up to four PCI-X bus masters
- PCI-X bus error reporting
- RAS features

Broadcom®, the pulse logo, Connecting everything®, the Connecting everything logo, NetXtreme®, and Smart Load Balancing™ are among the trademarks of Broadcom Corporation and/or its affiliates in the United States, certain other countries and/or the EU. Any other trademarks or trade names mentioned are the property of their respective owners.

Connecting
everything®



BROADCOM CORPORATION

5300 California Avenue
Irvine, California 92617

© 2009 by BROADCOM CORPORATION. All rights reserved.

5714C-PB03-R 04/15/09

Phone: 949-926-5000
Fax: 949-926-5203
E-mail: info@broadcom.com
Web: www.broadcom.com